

COMPOSITE POROUS MEMBRANE FOR SEPARATION AND PURIFICATION (JP... Page 1 of 1

544960-801

Select CR

DELPHION

Log Out Work Files Save Searches

My Account

Search: QuickNumber Boolean Advanced Derwent

Help

The Delphion Integrated View

Get Now: ☒ PDF | [File History](#) | [Other choices](#)Tools: [Add to Work File](#) | [Create new Work File](#)

Add

View: INPADOC | [Jump to: Top](#)

Go to: Derwent

☒ [Email this to a friend](#)

Title: JP62186904A2: COMPOSITE POROUS MEMBRANE FOR SEPARATION AND PURIFICATION

Derwent Title: Composite porous membrane for sepn. and purificn. - is obtd. by forming very thin conductive layer on surfaces of microporous membrane (Derwent Record)

Country: JP Japan

Kin: A DOC. LAID OPEN TO PUBL. INSPEC. [PUBLISHED FROM 1971 ON]

Inventor: SUGAI KIYOSHI;

Assignee: SUGAI KIYOSHI

[News, Profiles, Stocks and More about this company](#)

Published / Filed: 1987-08-15 / 1986-02-13

Application Number: JP1986000029297

IPC Code: Advanced: B01D 61/02; B01D 61/08; B01D 61/14; B01D 61/18; C08J 9/34; C08J 9/36;
Core: C08J 9/00; more...
IPC-7: B01D 13/00; B01D 13/02; C08J 9/36;

Priority Number: 1986-02-13 JP1986000029297

Abstract: PURPOSE: To obtain the titled composite porous membrane capable of accurately measuring a potential or a change in the electric current generated when used by forming an extremely thin electrically conductive layer on the surface of a membranous material having fine pores to make the surface potential freely controllable.

CONSTITUTION: The electrically conductive layer 2 such as a metallic layer is formed by sputtering on one surface of a porous membrane 1 of polysulfone, etc., having fine pores, and a lead wire is fixed to the end part of the metallic layer to produce a composite porous membrane having a metallic thin film electrode on one surface. The composite porous membrane is set between the chambers I and II of a device 10 as a diaphragm and used for filtration and separation. A fluid contg. fine particles or molecules to be separated such as a latex obtained by dispersing and stabilizing spherical particles of polystyrene with a nonionic surfactant is introduced under pressure into the chamber I from an inlet 11, and a voltage is impressed on the conductive layer 2 from the outside through the lead wire. The substance to be separated is permeated through the composite porous membrane, collected in the chamber II, and discharged from an outlet 14.

COPYRIGHT: (C)1987,JPO&Japio

Family: None

Other Abstract Info: DERABS C87-268003 DERC87-268003

[Nominate this for the Gallery...](#)

Powered by Verity

Copyright © 1997-2004 Thomson Reuters

[Subscriptions](#) | [Web Seminars](#) | [Privacy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact Us](#) | [Help](#)